

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)


PCT

(10) International Publication Number
WO 2005/083288 A1

- (51) International Patent Classification⁷: **F16D 41/08**, 15/00
- (74) Agent: MASSINA, Glenn, M.; Michael Best & Friedrich LLP, 100 East Wisconsin Avenue, Milwaukee, WI 53202-4108 (US).
- (21) International Application Number: PCT/US2005/005562
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 22 February 2005 (22.02.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/546,854 23 February 2004 (23.02.2004) US
- (71) Applicant (for all designated States except US): TIMKEN US CORPORATION [US/US]; 59 Field Street, Torrington, CT 06790 (US).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): JOKI, Mark, A. [US/US]; 5930 North American Road, Dover, OH 44622 (US).

[Continued on next page]

(54) Title: LOW DRAG MULTIMODE CLUTCH



(57) Abstract: A clutch device comprising a first member, a second member, a race member, and a slipper member. The first member (12) has a first conic surface and the second member (3) has a second conic surface (6) generally opposed to the first conic surface. The race member (13) is fixed to the first conic surface of said first member and the slipper (11) is positioned adjacent the second conic surface of the second member. The race and the slipper members have complementary projections (20, 22) to define pockets into which rollers (14) are arranged. The axial relationship of the first and second members is adjustable to control mating between the slipper (11) and the second conic surface (6) of the second member and thereby enable or prevent torque transmission between the first and second members.



Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BACKGROUND

5 The present invention relates to a clutch device. More particularly, the present invention relates to a multimode clutch device.

 Planetary gear automatic transmissions employ one-way clutches to simplify shifting. If a first planetary stage is transmitting power through a one-way clutch, a parallel connected second stage with a higher ratio can be engaged during a shift. The one-way clutch allows the output speed to increase without the first stage resisting the increased speed. The first planetary stage is however incapable of carrying negative torque because of the one-way clutch. If the one-way clutch can be selectively locked, additional ratios can be designed into the transmission without adding additional planetary stages. US patent 6,409,001 discloses a full complement multimode clutch that is capable of providing selectable one-way forward, one-way reverse, freewheeling, and locking modes. This clutch relies on a 'slipper' ring which must rub against a mating surface to provide a lockup. The present invention avoids the frictional losses of the slipper clutch in a freewheeling mode while still allowing mode control.

10
15
20

SUMMARY

 The present invention provides a clutch device comprising a first member, a second member, a race member, and a slipper member. The first member has a first conic surface and the second member has a second conic surface generally opposed to the first conic surface. The race member is fixed to the first conic surface of said first member and the slipper member is positioned adjacent the second conic surface of the second member. The race member has multiple longitudinal projections corresponding to similar

25

projections on the slipper member to define pockets into which rollers are arranged. The slipper member has a surface matable with the second conic surface of said second member. The axial relationship of the first and second members is adjustable to control mating between the slipper member and the second conic surface of the second member
5 and thereby enable or prevent torque transmission between the first and second members.

In at least one embodiment, the second member is a portion of a planet carrier of a planetary gear stage.

In a preferred embodiment of the present invention, the axial relationship between the first and second members is biased by spring force to prevent engagement and
10 hydraulic actuation is utilized to overcome the spring force to cause engagement.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a sectional view of a planetary reduction stage employing a device according to a first embodiment of the invention.

15 Figure 2 is a sectional view of the slipper clutch components of Figure 1.

Figures 3a-c are sectional views of the assembly steps of a preferred method of assembling the device according to the first embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 The present invention will be described with reference to the accompanying drawing figures wherein like numbers represent like elements throughout. Certain terminology, for example, "top", "bottom", "right", "left", "front", "frontward", "forward", "back", "rear" and "rearward", is used in the following description for relative descriptive clarity only and is not intended to be limiting.

Referring to Figure 1, a planetary reduction stage within a housing 1 comprises a multiplicity of planet gears 2 supported by planet carrier 3 by way of support pins 4 and engaged to a sun gear and ring gear (not shown). The planet carrier 3 is rotatably supported by bearings 8 and 9. Onto the planet carrier 3 is formed a conic outer peripheral surface 6 which preferably has a shallow angle. The angle is preferably in the range of 1-3 degrees, preferably 1.5 degrees, but can be of an angle less than 1 degree or greater than 3 degrees. Radially outward from the conic surface 6 is an outer body 12 rotatably supported in the housing 1 by bearing surfaces in the housing 1. Said outer body 12 includes a conic inner peripheral surface of angle similar to surface 6 onto which is fixed a ring shaped clutch outer race 13. A ring shaped slipper 11 is located radially inward from the outer race 13. While the preferred embodiment is described with the ring shaped clutch race fixed to the outer body 12 conic surface with the slipper positioned radially inward, it is also considered that the components may be reversed, with the ring shaped clutch race fixed to the conic surface 6 and the slipper positioned radially outward.

Referring to Figure 2, on the inner periphery of the outer race 13 and into the outer periphery of the slipper 11 are formed longitudinal projections 20, 22 radially opposing each other. These projections 20, 22 form pockets 24 into which cylindrical rollers 14 are placed. The slipper 11 has an opening 21 cut parallel to the slipper's 11 axis to facilitate radial contraction. The slipper 11 is manufactured to a diameter slightly larger than its mounted size to apply a radial preload force to the rollers 14. The outer race 13 and slipper 11 are generally uniform in section along a longitudinal section. Referring back to Figure 1, the outer race 13 and slipper 11 have flanges 26, 28 formed at the extremes of their widths to contain the rollers 14.

The axial location of the planet carrier 3, in it's free state, is determined by roller bearing 8 which is located by a shoulder 30 in a generally cylindrical projection from the housing 7 and a spring 10. In this free state, the slipper 11 is free of the conic outer surface 6 with a small clearance, about 40-80 microns, allowing low drag rotation of the planet carrier 3. A plate clutch 5 can cause torque transmission between the outer body 12 and the housing, 1. When such torque transmission is desired, hydraulic pressure is applied to the left side of piston 15, moving it against retraction spring 16 until it contacts the planet carrier 3 and moves the planet carrier 3 right against spring 10. The slipper 11 now rubs against the conic surface 6. The tangential force carried through the rollers 14 causes them to climb the sides of their pockets 24, contracting the slipper opening 21 until the slipper 11 stops against the conic surface 6. When the clearance is removed, the rollers 14 are contacting the races at a pressure angle of 83 to 88 degrees which causes locking of the slipper 11 on the conic surface 6 and a high torque transmission capability.

To accomplish an upshift, the pressure on the piston 15 is removed, causing the piston 15 to retract under force from spring 16. However, because of the high forces of the slipper 11 on the conic surface 6, the planet carrier 3 remains in the engaged position. A clutch elsewhere in the transmission applies torque to a higher gear stage causing a reduction in torque to the subject planet stage with the slipper clutch. As torque reaches zero, the contracting force from the rollers 14 on the slipper 11 disappears, and the slipper 11 expands under its prestress. With the slipper contact relieved, the planet carrier 3 moves away from the slipper 11 by force from spring 10 and the low drag freewheeling mode is active.

Referring to Figures 3a-c, a preferred method of assembly is shown. Referring to Figure 3a, the device is assembled by first installing the outer race 13 into the outer body 12 and the slipper 11 over the conic surface 6, then placing the outer body 12 around the

slipper 11. Referring to Figure 3b, the rollers 14 are placed between the outer race 13 and the slipper 11. Referring to Figure 3c, a split disk tool 17 is placed in the axial gap between the outer body 12 and the planet carrier 3 to resist the force of crimping the ends of the slipper 11 and the outer race 13, thereby restraining the rollers 14.

What is claimed is:

1. A clutch device comprising:
 - a first member having a first conic surface;
 - a second member concentric with the first member and having a second conic
 - 5 surface generally axially aligned with the first conic surface;
 - a race member fixed to the first conic surface; and
 - a slipper member positioned adjacent to the second conic surface in opposed
 - relation to the race member, the race and slipper members having complementary
 - projections to define pockets into which rollers are arranged,
 - 10 wherein the first and second members are axially adjustable relative to one another
 - between a first axial relationship in which the slipper is free of the second conic surface
 - and a second axial relationship in which the slipper contacts the second conic surface.
2. The clutch device according to claim 1 wherein the first member is radially
- 15 outward relative to the second member.
3. The clutch device according to claim 1 wherein the first member is radially
- inward relative to the second member.
- 20 4. The clutch device according to claim 1 wherein the second member is a
- portion of a planet carrier of a planetary gear stage.
5. The clutch device according to claim 1 wherein the first and second conic
- surfaces are each at angle in the range of 1 to 3 degrees.
- 25

6. The clutch device according to claim 5 wherein the first and second conic surfaces are each at angle of 1.5 degrees.

7. The clutch device according to claim 1 wherein the slipper member has an axial opening therethrough such that the slipper member is expandable or contractible.

8. The clutch device according to claim 7 wherein in the second axial relationship, the rollers are caused to climb the projections and thereby cause the slipper member to expand or contract into a fixed relationship with the second member second conic surface.

9. The clutch device according to claim 8 wherein in the second axial relationship, the rollers contact the projections at a pressure angle between 83 to 88 degrees.

15

10. The clutch device according to claim 1 wherein the slipper member is configured to apply a prestress against the rollers.

11. The clutch device according to claim 1 wherein the race member and slipper member each have axial edges provided with radial flanges to retain the rollers within the pockets.

12. The clutch device according to claim 1 wherein a spring biases one of the first or second members to the first axial relationship.

25

13. The clutch device according to claim 12 further comprising a fluid pressure source configured to selectively apply a fluid pressure force against the spring bias to move the first and second members in to the second axial relationship.

5 14. The clutch device according to claim 1 wherein in the first axial relationship a clearance in the range of 40-80 microns is provided between the slipper member and the second conic surface.

15. A method of forming a clutching device comprising the steps of:
10 providing a first member having a first conic surface;
fixing a race member to the first conic surface, the race member having a plurality of projections thereon and having a first axial end with a radially extending flange and a generally open second axial end;
providing a second member having a second conic surface;
15 providing a slipper member adjacent the second conic surface, the slipper member having a plurality of projections thereon and having a first axial end with a radially extending flange and a generally open second axial end;
positioning the first member relative to the second member such that the race member is opposed to the slipper member and the race and slipper member projections
20 define pockets;
positioning rollers in to the pockets; and
closing the race member second axial end and the slipper member second axial end to retain the rollers within the pockets.

16. The method according to claim 15 wherein the step of closing the race member second axial end and the slipper member second axial end includes providing a split disk tool adjacent to the race member first axial end and the slipper member first axial end.

5

17. The method according to claim 16 wherein the step of closing the race member second axial end and the slipper member second axial end includes crimping the race member second axial end and the slipper member second axial end.




FIG. 1




FIG. 2




FIG. 3a




FIG. 3b




FIG. 3c

INTERNATIONAL SEARCH REPORT

PCT/US2005/005562

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16D41/08 F16D15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 583 693 A (HENRY MARTIN KESTERTON) 24 December 1946 (1946-12-24) the whole document	1, 15
A	US 6 409 001 B1 (KERR JOHN HUGH) 25 June 2002 (2002-06-25) cited in the application column 7, line 1 - line 23; figures 8a, 8b	1, 7, 8, 15
A	US 2002/142878 A1 (BANSBACH ERIC A ET AL) 3 October 2002 (2002-10-03) paragraph '0030! - paragraph '0035!; figure 4a	1, 4, 12, 13
A	DE 101 58 608 A1 (LANGENBECK, KONRAD) 12 June 2003 (2003-06-12) paragraph '0017! - paragraph '0018!; figure 2	1
----- -/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

23 May 2005

Date of mailing of the international search report

31/05/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Overbeeke, J

INTERNATIONAL SEARCH REPORT

PCT/US2005/005562

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 3 746 136 A (MAROLA A,US ET AL) 17 July 1973 (1973-07-17) column 1, line 68 - column 2, line 32; figures 1,2,7</p> <p>-----</p>	15

INTERNATIONAL SEARCH REPORT

PCT/US2005/005562

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 583693	A	24-12-1946	NONE
US 6409001	B1	25-06-2002	AT 244364 T 15-07-2003
		AU 1221099 A	16-06-1999
		BR 9815027 A	03-10-2000
		CA 2315875 A1	10-06-1999
		DE 69816118 D1	07-08-2003
		DE 69816118 T2	08-01-2004
		EP 1038117 A1	27-09-2000
		JP 2001525518 T	11-12-2001
		AT 236361 T	15-04-2003
		AT 206806 T	15-10-2001
		AU 1220999 A	16-06-1999
		AU 1327999 A	16-06-1999
		BR 9815407 A	17-10-2000
		BR 9815408 A	10-10-2000
		CA 2315873 A1	10-06-1999
		CA 2315874 A1	10-06-1999
		WO 9928644 A1	10-06-1999
		WO 9928645 A1	10-06-1999
		WO 9928659 A1	10-06-1999
		DE 69802010 D1	15-11-2001
		DE 69802010 T2	11-07-2002
		DE 69813028 D1	08-05-2003
		DE 69813028 T2	25-09-2003
		EP 1049883 A1	08-11-2000
		EP 1038125 A1	27-09-2000
		JP 2001525517 T	11-12-2001
		JP 2001525523 T	11-12-2001
		US 6367604 B1	09-04-2002
		US 6446776 B1	10-09-2002
US 2002142878	A1	03-10-2002	NONE
DE 10158608	A1	12-06-2003	NONE
US 3746136	A	17-07-1973	AU 459295 B2 05-03-1975
		AU 3914672 A	23-08-1973
		CA 950388 A1	02-07-1974
		DE 2212507 A1	16-11-1972
		FR 2135643 A5	22-12-1972
		GB 1371989 A	30-10-1974
		IT 950785 B	20-06-1973
		SE 375834 B	28-04-1975
		US 3820640 A	28-06-1974